

Fabrication Alternatives:	ERW, HF, DSAW/SAWL, SMLS, HSAW
OD:	ERW: 2.375" through 30" HF: 0.840" through 24" DSAW/SAWL: 12.75" through 144" SMLS: 2.375" through 26" HSAW: 8.625" through 144"
Wall Ranges:	ERW: 0.154" through 0.750" HF: 0.120" through 1.000" DSAW/SAWL: 0.250" through 6.000" SMLS: 0.219" through 2.500" HSAW: 0.250" through 1.000"
Lengths:	Single Random Double Random Custom lengths are also available
Surface Finishes:	Bare, Oiled, Mill Varnish, Galv, FBE, FBE Dual, 3LPE, 3LPP, Coal Tar Enamel, Tape Wrap, Paper Wrap, Cement Mortar, Liquid Epoxy Lining and Glass Cloth. Vertical Slotting available up to 0.500" w/t
End Finishes:	Beveled, Square Cut, Bell & Spigot, Flanged, Victaulic, Threaded & Coupled.
Additional Services:	Vertical and Horizontal Slotting

Standard Pipe

- A53 Grades A/B, ASTM A106 Grades B/C
- AWWA, C200, ASTM A139, ASTM A120, API 5L-B
- ASTM A671, A672 (Stress Relieved, Normalized and/or Tempered) in Various Classes